

Flat Bed With Sides and Upper Sides

SUSPENSION AND PNEUMATICS	HEIGHTS in mm					WEIGHT in kg			
	H maxi	J empty	J loaded	G maxi	L	PM	C U +/- 3%	P 1	P 2
Balancing pole mechanic 12.00 R 20 PR 18	1 500	1420	1320	1475	12500	7000	31000	17000	21000

Technical Specifications

Use:

- Vehicles conceived for the transport of uniformly retort loads.
- They cannot be used for localized loads or with excess without the authorization of the constructor.

Flat bed:

Frame made of:

- Two rectilinear girders in I section in a mechanically-welded construction. Flat iron wings E 36 quality and Ame in 6 mm thickness in E 24-2, with a swan neck ISO 1726 adapting to all types of tractors.
- Crossbars in folded sheet metal rigidly spacing the two girders.
- 10 mm thickness fastening plate with double position.

Suspension and trucks:

Normal Tandem type composed of the following elements:

- Mechanical suspension with 4 multi-blades laminated springs in manganate-silica steel.
- Two axles with tubular bodies, made of treated steel XC 32, load at ground 12T each, disc hub for 20''.
- Traction bars elevated on vibration dampers, one is fixed and the other is adjustable by axles.
- Mechanical drum braking, in melting commanded by an expander in S.
- Eight (8) pneumatics 1200 x 20 PR 18.
- Twinned assembling, on a disc wheel 20 x 8,5.

Equipments :

- Air compressed brakes in two lines with automatic corrector, conform to the existing standards.
- Cam remote control ensured by the automatic remedial lever.
- Park brakes with cable.
- 24V complete installation of lights and markings conform to the Highway Code.
- Two speeds vertical telescopic support.
Lifting capacity: 24 T.
Static capacity: 50 T.

- Dismantling kingpin 2 '' interchangeable at 3''1/2.
- 1 Back anti-fitting bumper.
- 1 Spare wheel support.
- 1 Spare wheel.
- 7 brelage rollers and side hooks.0.
- 1 Tool box at the back and a large size one on the side.
- Rear wings with rubber mud flaps.
- Wheel lever key.
- Use and maintenance guide.

Presentation and painting:

The whole is presented in :

- Two primary painting coats.
- Two finishing painting coats: standard colour.

Options:

- Side panels coachbuilding, height: 800 mm.
- Crate coachbuilding: 700 mm.
- Bolt container.
- Ranchers set.
- Available in all colours.
- Pneumatic 13 R 22.5 (tubeless).